# **Operation Guide 2957**

# CASIO.

### **About This Manual**




- . Depending on the model of your watch, display text appears either as dark figures on a light background or light figures on a dark background. All sample displays in this manual are shown using dark figures on a light
- Button operations are indicated using the letters show in the illustration.

  Each section of this manual provides you with the
- information you need to perform operations in each mode. Further details and technical information can be found in the "Reference" section.



### **General Guide**

- Press © to change from mode to mode.
  In any mode, press (L) to illuminate the display.



### Timekeeping

Day of week THU 10:5850 6:30 Month - Day

Use the Timekeeping Mode to set and view the current time and date.


Read This Before You Set the Time and Date!
The times displayed in the Timekeeping Mode and World
Time Mode are linked. Because of this, make sure you
select a city code for your Home City (the city where you
normally use the watch) before you set the time and date.

Hour: Minutes Seconds

## To set the time and date



- 1. In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting screen.
- Press © to move the flashing in the sequence shown below to select other settings.



3. When the setting you want to change is flashing, use (1) and (8) to change it as

Screen	To do this:	Do this:			
50	Reset the seconds to 00	Press D.			
OFF	Toggle between Daylight Saving Time (CT) and Standard Time (CFF)	Press D.			
TYO	Change the city code	Use (D) (east) and (B) (west).			
° 10:58	Change the hour or minutes	Use (D) (+) and (B) (-).			
15H	Toggle between 12-hour (12H) and 24-hour (2HH) timekeeping	Press D.			
2005	Change the year	Use (D) (+) and (B) (-).			
6-30	Change the month or day				

- For full information on city codes, see the "City Code Table".

  See "Daylight Saving Time (DST)" for details about DST setting.

  Press (A) to exit the setting screen.

  With the 12-hour format, the P (PM) indicator appears on the display for times in the range of noon to 11:59 p.m. and the A (AM) indicator appears for times in the range of midnight to 11:59 a.m.

  With the 24-hour format, times are displayed in the range of 0:00 to 23:59, without any indicator.
- any indicator.
   The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is
- The day of the week is automatically displayed in accordance with the date (year, month, and day) settings.

### Daylight Saving Time (DST)

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight



- To toggle the Timekeeping Mode time between DST and Standard Time

  1. In the Timekeeping Mode, hold down (a) until the seconds start to flash, which indicates the setting
  - screen.

    2. Press © to display the DST setting screen.

    3. Press © to toggle between Daylight Saving Time (£F displayed) and Standard Time (£F displayed).

     Note that you cannot switch between Standard Time and Daylight Saving Time while £MT is selected as the Home City code.

    4. Press © to exit the setting screen.

     The DST indicator appears on the display to indicate that Daylight Saving Time is turned on.

### e-DATA MEMORY



You can use the watch's e-DATA MEMORY to store e-mail addresses, Web page URLs, and other text data. You can also use a password to limit access to e-DATA MEMORY contents

All of the operations in this section are performed in the e-DATA MEMORY Mode, which you enter by pressing ©.

### e-DATA MEMORY Management

e-DATA MEMORY can hold up to 315 characters total, while each record can contain up to 63 characters. The maximum number of records depends on the number of betreeters are presented to be a betreeter or the number of the numbe

- characters per record, as shown below.

   63 characters per record: 5 records

   7 or fewer characters per record: 40 records



- To create a new e-DATA MEMORY record

  1. In the e-DATA MEMORY Mode, press ① and ⑧ at the same time to display the remaining memory, to reen.

   If ② is shown for remaining memory, it means that memory is full. To store another record, you will first
  - have to delete some of the records stored in memory

  - anave to delete some of the records stored in memory.

    2. Hold down (≜) until the flashing cursor (≡) appears on the display, which indicates the setting screen.

     The setting screen also shows the record number that is automatically assigned to the new record.


    3. Input the text you want.

     When inputting the text, use (⊕) (+) and (⊕) (-) to cold through characters at the current cursor.
  - cycle through characters at the current curso location, and ⑤ to move the cursor to the right. See "Inputting Text".

    4. Press ⑥ to store your data and return to the e-DATA MEMORY record screen (without the cursor).
- Pressing (a) causes the message SET to appear for about two seconds as the data is stored. After that, the e-DATA MEMORY record screen appears.
- The text can show only three characters at a time, so longer text scrolls continuously from right to left. The last character is indicated by the symbol 4 after it. Press (A) to stop and restart scrolling.

  Records are stored in memory in the sequence they are created.

**To recall e-DATA MEMORY records** In the e-DATA MEMORY Mode, use 0 (+) and 8 (-) to cycle through e-DATA MEMORY records as shown below.



Remaining Memory Screen



- The value on the remaining memory screen is the percentage of memory that is still available. It does not indicate the number of records that can be stored.
  The Password Setting screen shows ---- when a password is already registered.
- You can use the Password Setting screen to register, edit, or delete your password See "Using a Password to Protect e-DATA MEMORY Data" for more information.

- To edit an e-DATA MEMORY record

  1. In the e-DATA MEMORY Mode, use ① (+) and ③ (-) to display the record you want to edit.

  2. Hold down ④ until the flashing cursor appears on the display.

- Use ⓒ to move the flashing to the character you want to change.
   Use ⑥ (+) and ⑧ (-) to change the character.
   After making the changes you want, press ⑧ to store them and return to the e-DATA MEMORY record screen.

- o delete an e-DATA MEMORY record . In the e-DATA MEMORY Mode, use 0 (+) and 8 (-) to display the record you

- want to delete.

  2. Hold down (a) until the flashing cursor appears on the display.

  3. Press (a) and (b) at the same time to delete the record.

   The message CLLR appears to indicate that the record is being deleted. After the record is deleted, the cursor appears on the display, ready for input.

  4. Input data or press (a) to return to the remaining memory screen.

### Using a Password to Protect e-DATA MEMORY Data

You can register a 4-digit password to keep e-DATA MEMORY data secure.

Use a 4-digit password that is easy for you to remember, but difficult for others to decipher. If you forget the password, you will have to have your watch initialized (which deletes all data in memory) in order to access the e-DATA MEMORY again. To have the watch initialized, contact the store or dealer where you purchased it, and ask to have the AC operation performed.



- ord

  1. In the e-DATA MEMORY Mode, use ⑩ (+) and ⑯ (-) to display the Password Setting screen.

   This displays a screen that shows ≤ET PR\$5.

  2. Hold down ⑭ for about one second until NeW appears, with the first ❶ flashing.

   This is the New Password Setting screen.

  3. Use ⑪ (+) and ⑯ (-) to scroll through numbers at the first digit.
- 4. When the first digit is the number you want, press © to advance to the next digit.
  5. Repeat steps 3 and 4 to input all four digits of the password you want.

   Pressing @ wile inputting a new password clears your input and returns to the password Settine control.
- Password Setting screen
- 6. After all four of the password digits are the way you want, press © to register
- 6. After all four or the password sign.

   Pressing © causes the message SET to appear for about one second as the password is stored. After that, the Password Setting screen appears.

   After registering a password, you can input, recall, edit and delete data, if you want. After you exit the e-DATA MEMORY Mode, you will have to input the password

### To input the password



- Enter the e-DATA MEMORY Mode.
   On the Password Input screen (---- PR55), press ①
   or ③. This causes the first digit of the password to
- 3. Input the password

- 3. Input the password.
  Use ① (+) and ⑧ (-) to scroll through numbers at each digit.
  Press ② to advance to the next digit.
  Pressing ② while inputting the password clears your input and returns to the Password Input screen.
  4. After the password is the way you want, press ②.
  If the input password matches the one registered, the message ○K! appears, followed by an e-DATA MEMORY screen.
  If the password does not match, the message ERR appears, followed by the Password Input screen.

- To change the password

  1. Enter the e-DATA MEMORY Mode by inputting the current password.

  2. Use ⑩ (+) and ⑯ (−) to display the Password Setting screen.

  3. Perform the procedure starting from step 2 under "To register a new password" to specify the new password.

- To delete the password

  1. Enter the e-DATA MEMORY Mode by inputting the current password.

  2. Use ⑤ (+) and ⑥ (−) to display the Password Setting screen.

  3. Hold down ⑥ for about one second until NEW appears, with the first ℂ flashing.

  4. Press ⑧ and ⑥ at the same time to delete the password.

   The message □LR appears to indicate that the password is being deleted. After the password is deleted, the Password Setting screen appears.

### **World Time**



10:58

World Time shows the current time in 27 cities (29 time

around the world.
 All of the operations in this section are performed in the World Time Mode, which you enter by pressing ③.

To view the time in another city code In the World Time Mode, press () to scroll through city codes (time zones) to the east or () to scroll to the west.

For full information about city codes, see the \*City Code

- If the current time shown for a city is wrong, check your Timekeeping Mode time and Home City code settings and make the necessary changes.

  When the currently selected time zone is one that includes mostly ocean, a value indicating the zone's Greenwich Mean Time differential appears in place of a city code.

- To toggle a city code time between Standard Time and Daylight Saving Time

  1. In the World Time Mode, use (a) and (b) to display the city code (time zone) whose Standard Time/Daylight Saving Time setting you want to change.

  2. Hold down (a) for about one second to toggle Daylight Saving Time (DST displayed) and Standard Time (DST one) displayed).

  - not displayed).
    The **DST** indicator is on the display whenever you display a city code for which Daylight Saving Time is turned on.
  - Note that the DST/Standard Time setting affects only the currently displayed city code. Other city codes are not
  - Note that you cannot switch between Standard Time and Daylight Saving Time while GMT is selected as the city code.

### **Alarms**



You can set up to five independent multi-function alarms with hour, minutes, month, and day. When an alarm is turned on, the alarm tone sounds when the alarm time is reached. One of the alarms is a snooze alarm, while the other four are one-time alarms. You can also input reminder text that appears when the alarm time is

reached.
You can also turn on an Hourly Time Signal that causes the watch to beep twice every hour on the hour.

• There are five alarm screens numbered AlL 1 through

- AL4 for the one-time alarm, a snooze alarm screen
- HL4 for the one-time alarm, a shooze alarm screen indicated by SNZ. The Hourly Time Signal screen is indicated by SIG.

  In the case of the snooze alarm screen, the snooze alarm indicator (sweet) appears in the lower right corner of the display.
- Alarm settings (and Hourly Time Signal settings) are available in the Alarm Mode, which you enter by pressing (C).

### Alarm Types

The alarm type is determined by the settings you make, as described below

### Daily alarm

Set the hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set.

# Date alarm

Set the month, day, hour and minutes for the alarm time. This type of setting causes the alarm to sound at the specific time, on the specific date you set.

## • 1-Month alarm

Set the month, hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set, only during the month you set.

### Monthly alarm

Set the day, hour and minutes for the alarm time. This type of setting causes the alarm to sound every month at the time you set, on the day you set.



1. In the Alarm Mode, use (D) and (B) to scroll through the alarm screens until the one whose time you want to set is displayed.



- To set a one-time alarm, display one of the screens indicated by an alarm number from RL 1 through RL 4. To set the snooze alarm, display the screen indicated by the scr To set a one-line attain, obsplay one of unle screens indicated by an attainful from PL.1 through FiL.4. To set the snooze alarm, display the screen indicat by SNZ.
   The snooze alarm repeats every five minutes.
   After you select an alarm, hold down ♠ until the hour setting of the alarm time
- starts to flash, which indicates the setting screen.

  This operation automatically turns on the alarm.

  Press © to move the flashing in the sequence shown below to select other settings.



- Selecting the text causes the text input cursor (■) to appear. There are eight spaces in the text, so you have to press ⓒ eight times to move to the Hour
- 4. While a setting is flashing, use (D), (B), and (C) to change it as described below

	3, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,							
Screen	To do this:	Do this:						
^ 12:00	Change the hour and minutes	Use (i) (+) and (ii) (-).  • With the 12-hour format, set the time correctly as a.m. (A indicator) or p.m. (P indicator).						
	Change the month and day	To set an alarm that does not include a month and/or day, set - for each setting.						
	Input reminder text	Use (1) (+) and (8) (-) to cycle through characters at the current cursor location, and (2) to move the cursor to the right. See "Inputting Text".						

# **Operation Guide 2957**



• Pressing (a) and (b) at the same time while any setting is flashing automatically sets the time to AM12:00 and the date to ----. It also clears any text that is input for the alarm



5. Press (A) to exit the setting screen.
If you input reminder text, the text appears in place of the alarm number.
If the reminder text is more than three characters, it will scroll form right to left.

If the alarm has a month and/or day setting, the month/ day appears at the bottom of the display, in place of the Timekeeping Mode time.

### Alarm Operation



All of the graphic area segments start to flash, starting from the point the Timekeeping Mode time reaches one hour before an alarm time. This pre-alarm feature lets you know that an alarm time is about to be reached.

The alarm tone sounds at the preset time for 10 seconds. regardless of the mode the watch is in. In the case of the snooze alarm, the alarm operation is performed a total of seven times, every five minutes, until you turn the alarm

- To stop the alarm tone after it starts to sound, press any
- The pre-alarm feature works in the Timekeeping Mode only. To stop the pre-alarm after it starts, press any button. Note, however, that pressing © also changes to the e-DATA MEMORY Mode
- If you input reminder text for an alarm, the text appears for one minute on the Timekeeping Mode screen when the alarm time is reached. You can clear the reminder text display by pressing (A), (B), or (D), or by exiting the Timekeeping
- In the case of the snooze alarm, the reminder text appears on the Timekeeping
- In the case of the snooze alarm, the reminder text appears on the Timekeeping Mode screen for the initial alarm operation only.
   Performing any one of the following operations during a 5-minute interval between snooze alarms cancels the current snooze alarm operation. Displaying the Timekeeping Mode setting screen Displaying the SNZ setting screen Changing the DST setting of the Home City code in the World Time Mode

In the Alarm Mode, hold down (D) to sound the alarm.



- . In the Alarm Mode, use 

  and 

  B to select an alarm. 2. Press (A) to toggle it on and off.
  Turning on a alarm (AL1 to AL4, or SNZ) displays
- the alarm on indicator (ALM) on its Alarm Mode
- In all modes, the alarm on indicator is shown for any alarm that is currently turned on.

  The alarm on indicator flashes while the alarm is
- sounding.
   The snooze alarm indicator ((a) flashes while the snooze alarm is sounding and during the 5-minute intervals between alarms.



Hourly time signal or

- - The Hourly Time Signal on indicator (Signar) is shown on the display in all modes while this function is turned

### Countdown Timer



You can set the countdown timer within a range of one minute to 24 hours. An alarm sounds when the countdown reaches zero.

- You can also select auto-repeat, which automatically You can also select auto-repeat, which automatically restarts the countdown from the original value you set whenever zero is reached.

  The initial default countdown start time when you purchase the watch or after you have its battery replaced is 15 minutes.
- Countdown timer functions are available in the Countdown Timer Mode, which you can enter using ©

- To use the countdown timer
  Press 
   while in the Countdown Timer Mode to start the countdown timer.

  When the end of the countdown is reached and auto-repeat is turned off, the alarm sounds for 10 seconds or until you stop it by pressing any button. The countdown time is automatically reset to its starting value after the alarm stops.

  When the end of the countdown is reached and auto-repeat is turned on, the alarm sounds, but the countdown starts again automatically whenever the countdown reaches zero.

  The countdown timer measurement operation continues even if you exit the Countdown Timer Mode.


  Press 
   while a countdown operation is in progress to pause it. Press 
   again to resume the countdown.

- resume the countdown.
- To completely stop a countdown operation, first pause it (by pressing ®), and then
  press ®. This returns the countdown time to its starting value.

### To set up the countdown time



- timer
  L. While the countdown start time is on the display in the Countdown Timer Mode, hold down (a) until the hour setting of the countdown start time starts to flash, which indicates the setting screen.
  If the countdown start time is not displayed, use the procedure "To use the countdown timer" to display it.
  2. Press (a) to move the flashing in the sequence shown below to select other settings.
- below to select other settings



3. While a setting is flashing, use (D) and (B) to change it as described below

Screen	To do this:	Do this:			
0: 15	Change the hours or minutes	Use (D) (+) and (B) (-).			
OFF	Toggle auto-repeat on (@ff) and off (@FF)	Press D.			

- To specify a countdown start time of 24 hours, set 3:33.

  4. Press (a) to exit the setting screen.

  The auto-repeat on indicator ((3)) appears on the display while this function is turned on.

  Frequent use of auto-repeat and the alarm can run down battery power.

### Stopwatch




The stopwatch lets you measure elapsed time, split times, and two finishes.

- The display range of the stopwatch is 23 hours, 59 minutes, 59.99 seconds.

- 59 minutes, 59.99 seconds.
  The stopwatch continues to run, restarting from zero after it reaches its limit, until you stop it.
  The stopwatch measurement operation continues even if you exit the Stopwatch Mode.
  Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to
- elapsed time measurement. All of the operations in this section are performed in the

# Stopwatch Mode, which you enter by pressing ©



The time on the screen may not appear to stop immediately when you press a button to stop timing or to perform a split operation. Despite this, the time recorded by your button operation is accurate.

### **Backlight**



The backlight uses an EL (electro-luminescent) panel that causes the entire display to glow for easy reading in the dark. The watch's auto light switch automatically turns on the backlight when you angle the watch towards your

- The auto light switch must be turned on (indicated by The auto light switch on indicator) for it to operate.
   See "Backlight Precautions" for other important information about using the backlight.

To turn on the backlight manually In any mode, press  $\bigcirc$  to illuminate the display for about one second.

 The above operation turns on the backlight regardless of the current auto light switch setting.

### About the Auto Light Switch

Turning on the auto light switch causes the backlight to turn on for about one second, whenever you position your wrist as described below in any mode.

Moving the watch to a position that is parallel to the ground and then tilting it towards you at more than 40 degrees causes the backlight to turn on.

• Wear the watch on the outside of your wrist.



- varning:
  Always make sure you are in a safe place whenever you are reading the display of the watch using the auto light switch. Be especially careful when running or engaged in any other activity that can result in accident or injury. Also take care that sudden illumination by the auto light switch does not
- Also take care in a souder mullimation by the auto light switch does not startle or distract others around you. When you are wearing the watch, make sure that its auto light switch is turned off before riding on a bicycle or operating a motorcycle or any other motor vehicle. Sudden and unintended operation of the auto light switch can create a distraction, which can result in a traffic accident and serious personal injury.

# **Operation Guide 2957**

# CASIO

- To turn the auto light switch on and off
  In the Timekeeping Mode, hold down ① for about one second to toggle the auto light
  switch on (♠ displayed) and off (♠ not displayed).

  The auto light switch on indicator (♠) is on the display in all modes while the auto
  light switch is turned on.

  In order to protect against running down the battery, the auto light switch
  automatically turns off approximately six hours after you turn it on. Repeat the above
  procedure to turn the auto light switch back on if you want.

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

### Graphic Area

- The following describes the information indicated by the graphic area in each mode.

  In the Timekeeping Mode, World Time Mode, and Alarm Mode, the graphic area indicates the passage of each second of the current time (Timekeeping Mode time).

  In the e-DATA MEMORY Mode, the graphic area indicates the number at the
- flashing digit during password input.

  In the Countdown Timer Mode, the graphic area indicates the passage of each second of the countdown.
- In the Stopwatch Mode, the graphic area indicates the passage of each 1/10 second of the elapsed time.




### Inputting Text



The following describes how to input text in the e-DATA MEMORY and Alarm Modes.

To input characters

1. When the cursor is on the display, use ① and ⑧ to cycle through the available letters, numbers and symbols, in the sequence shown below.



- 2. When the character you want is at the cursor position, press © to move the cursor to the right.
- 3. Repeat steps 1 and 2 to input the rest of the characters you want . See the "Character List" for information about the characters you can input

- If you leave the watch in the e-DATA MEMORY or Alarm Mode for two or three minutes without performing any operation, it automatically changes to the
- Timekeeping Mode.

  If you leave a screen with flashing digits or a cursor on the display for two or three minutes without performing any operation, the watch automatically exits the setting screen. Except for password input, any settings you have made up to that point are saved automatically

## Scrolling

The (B) and (D) buttons are used in various modes and setting screens to scroll through data on the display. In most cases, holding down these buttons during a scroll operation scrolls at high speed

### Initial Screens

When you enter the e-DATA MEMORY, World Time, or Alarm Mode, the data you were viewing when you last exited the mode appears first.

- Resetting the seconds to 30 while the current count is in the range of 30 to 59 causes the minutes to be increased by 1. In the range of 00 to 29, the seconds are reset to 30 without changing the minutes.
- The year can be set in the range of 2000 to 2039.
  The watch's built-in full automatic calendar makes allowances for different month lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced.

### **World Time**

- The current time in all World Time Mode cities is calculated in accordance with the Greenwich Mean Time (GMT) differential for each city, based on the current Home City time setting in the Timekeeping Mode.

  The seconds count of the World Time is synchronized with the seconds count of the Timekeeping Mode.

  The GMT differential is the time difference of the time zone where the city is located from Greenwich Mean Time.

- from Greenwich Mean Time GMT differential is calculated by this watch based on Universal Time Coordinated

### **Backlight Precautions**

- The electro-luminescent panel that provides illumination loses power after very long
- The illumination provided by the backlight may be hard to see when viewed under
- direct sunlight.

  The watch may emit an audible sound whenever the display is illuminated. This is due to vibration of the EL panel used for illumination, and does not indicate
- The backlight automatically turns off whenever an alarm sounds.
- Frequent use of the backlight shortens the battery life.

Auto light switch precautions

• Wearing the watch on the inside of your wrist and movement or vibration of your arm can cause the auto light switch to activate and illuminate the display. To avoid running down the battery, turn off the auto light switch whenever engaging in activities that might cause frequent illumination of the display.



- The backlight may not light if the face of the watch is more than 15 degrees above or below parallel. Make sure that the back of your hand is parallel to the ground. The backlight turns off in about one second, even if you
- The backlight turns off in about one second, even it you keep the watch pointed towards your face.
   Static electricity or magnetic force can interfere with proper operation of the auto light switch. If the backlight does not light, try moving the watch back to the starting position (parallel with the ground) and then till it back toward you again. If this does not work, drop your arm all the way down so it hangs at your side, and then bring it back up again. it back up again.
- Under certain conditions, the backlight may not light until about one second after you turn the face of the watch towards you. This does not necessarily indicate malfunction of the backlight.
   You may notice a very faint clicking sound coming from the watch when it is shaken back and forth. This sound is caused by mechanical operation of the auto light switch, and does not indicate a problem with the watch.

### Character List

7116	arac	ıcı	LIST										
а	a.	n	n	Α	FI	N	N	0	Ø	@	æ	"	**
b	ь	0	0	В	₿	0	0	1	1	~	74.7	^	^
С	C	р	p	С	C	Р	P	2	2	/	/	&	8:
d	d	q	q.	D	D	Q	0:	3	3	١	N	=	===
е	9	r	۳	Е	E	R	R	4	4	?	?	+	+
f	+	s	S	F	F	S	S	5	5	#	#	(	(
g	9	t	t	G	6	Т	T	6	6	1		)	)
h	h	u	u	Н	Н	U	U	7	7	%	76		
i	i	٧	V	1	I	٧	V	8	8				
j	<i>j</i>	W	W	J	J	W	W	9	9	:	:		
k	K	Х	X	K	K	Χ	X	*	380	;	- 2		
1	Į.	у	У	L	L	Υ	Υ	-		,	7		
m	m	Z	Z	М	М	Z	Z	_		,	2		

### City Code Table

City Code	City	GMT Differential	Other major cities in same time zone				
		-11.0	Pago Pago				
HNL	Honolulu	-10.0	Papeete				
ANC	Anchorage	-09.0	Nome				
LAX	Los Angeles	-08.0	San Francisco, Las Vegas, Vancouver, Seattle/Tacoma, Dawson City				
DEN	Denver	-07.0	El Paso, Edmonton				
CHI	Chicago	-06.0	Houston, Dallas/Fort Worth, New Orleans, Mexico City, Winnipeg				
NYC	New York	-05.0	Montreal, Detroit, Miami, Boston, Panama City, Havana, Lima, Bogota				
CCS	Caracas	-04.0	La Paz, Santiago, Port Of Spain				
RIO	Rio De Janeiro	-03.0	Sao Paulo, Buenos Aires, Brasilia, Montevideo				
		-02.0					
		-01.0	Praia				
GMT		+00.0	Dublin, Lisbon, Casablanca, Dakar, Abidian				
LON	London	+00.0	Dublin, Lisbon, Casabianca, Dakar, Abiujan				
PAR	Paris	+01.0	Milan, Rome, Madrid, Amsterdam, Algiers, Berlin, Hamburg, Frankfurt, Vienna, Stockholm				
CAI JRS	Cairo Jerusalem	+02.0	Athens, Helsinki, Istanbul, Beirut, Damascus, Cape Town				
JED	Jeddah	+03.0	Kuwait, Riyadh, Aden, Addis Ababa, Nairobi, Moscow				
THR	Tehran	+03.5	Shiraz				
DXB	Dubai	+04.0	Abu Dhabi, Muscat				
KBL	Kabul	+04.5					
KHI	Karachi	+05.0	Male				
DEL	Delhi	+05.5	Mumbai, Kolkata				
DAC	Dhaka	+06.0	Colombo				
RGN	Yangon	+06.5					
BKK	Bangkok	+07.0	Jakarta, Phnom Penh, Hanoi, Vientiane				
HKG	Hong Kong	+08.0	Singapore, Kuala Lumpur, Beijing, Taipei, Manila, Perth, Ulaanbaatar				
TYO	Tokyo	+09.0	Seoul, Pyongyang				
ADL	Adelaide	+09.5	Darwin				
SYD	Sydney	+10.0	Melbourne, Guam, Rabaul				
NOU	Noumea	+11.0	Port Vila				
WLG	Wellington	+12.0	Christchurch, Nadi, Nauru Island				

\*Based on data as of December 2004