CASIO

ENGLISH

Congratulations upon your selection of this CASIO watch.

 Note that the product illustrations in this manual are intended for reference only, and so the actual product may appear somewhat different than depicted by an illustration

This watch does not have a city code that corresponds to the UTC offset of -3.5 hours. Because of this, the radio-controlled atomic timekeeping function will not display the correct time for Newfoundland, Canada.

E-1

Warning!

- The measurement functions built into this watch are not intended for taking measurements that require professional or industrial precision. Values produced by this watch should be considered as reasonable representations only.
- To ensure correct direction readings by this watch, be sure to perform bidirectional calibration before using it. The watch may produce incorrect direction readings if you do not perform bidirectional calibration. For more information, see "To perform bidirectional calibration." (page E-56).

 Note that CASIO COMPUTER CO., LTD. assumes no responsibility for any damage or loss suffered by you or any third party arising through the use of this product or its maffurction.
- product or its malfunction.

About This Manual



Operations are performed using the watch's crown, and the three buttons indicated by the letters (A), (B) and (C) in this manual.

Hands and Indicators

- 1 Hour Hand
- Second Hand 3 Minute Hand
- 4 Upper Dial Hand: Indicates a time, in 24-hour format, depending on the current mode
- 5 Lower Dial Hand: Indicates the current mode.
- 6 Day Indicator

This User's Guide uses numbers shown above to identify

Using the Crown

This watch has a lock-type crown.

 You should normally have the crown locked during normal daily use. Leaving the crown unlocked creates the risk of unintended operations or even damage due to impact.

To lock the crown





1. Push the crown back in (see "To pull out, rotate, or push the

- Note that attempting to lock the crown when it is not pushed in can cause unexpected watch operation.
- 2. Rotate the crown so any one of its three grooves is aligned with Mark 1.
- 3. While pushing in on the crown (a), rotate it to the right (b) until it stops, and align the groove with Mark 2.

4. Gently pull on the crown to make sure it is securely locked and does not come out.

To unlock the crown

Rotate the crown so the groove aligns with Mark 1.

To pull out, rotate, or push the crown in

Important!

Before performing any of these operations, first unlock the crown.

The illustrations below show the different crown operations.

Pull out	Rotate	Push in

E-5

When rotating the crown to move the hands of the watch, you can use the operations described below to move the hands at high speed, either forward or back. There are two high-speed levels: HS1 and HS2 (faster than HS1).



While the crown is pulled out, rotate it rapidly a number of turns away from you (for forward movement) or towards you (for reverse movement).

To start HS2 high-speed movement



While HS1 high-speed forward movement is in progress, rotate the crown rapidly again a number of turns away from you.

To stop high-speed movement




Rotate the crown in the direction that is opposite that of the current high-speed movement or press any button.

- If you do not perform any operation for more than two minutes after pulling out the crown, crown operations will become disabled automatically. If this happens, push the crown back in and then pull it out again to re-enable crown operations.
 You can use high-speed hand movement when configuring time settings in the Timekeeping Mode, Alarm Mode, or Countdown Timer Mode.
- Button operations become disabled after you perform a crown operation. If this happens, rotate the crown slightly. This should restore button operations.

Things to check before using the watch

1. Hold down © at least two seconds to enter the Timekeeping Mode, and then observe the movement of the 2 Second Hand.



2. Check the Home City.

Use the procedure under "To configure Home City settings" (page E-36) to configure your

Important!

 Proper time calibration signal reception depends on correct Home City, time, and day settings in the Timekeeping Mode. Make sure you configure these settings correctly.

3. Set the current time.

- To set the time using a time calibration signal
 See "To get ready for a receive operation" (page E-25).
 To set the time manually
 See "Configuring Current Time and Day Settings Manually" (page E-41).

The watch is now ready for use.
• For details about the watch's radio controlled timekeeping feature, see "Radio Controlled Atomic Timekeeping" (page E-20).

F-8

CASIO

F-11

Contents

About This Manual

Using the Crown

E-4 To lock the crown

To unlock the crown

E-5 To pull out, rotate, or push the crown in

E-8 Things to check before using the watch

E-14 Charging the Watch

E-19 To recover from the sleep state

Radio Controlled Atomic Timekeeping F-25 To get ready for a receive operation

E-28 To perform manual receive

To check the result of the latest receive operation

E-30 To turn auto receive on and off

F-10

E-32 Mode Reference Guide

E-33 To determine the watch's current mode

To return to the Timekeeping Mode from any other mode

E-34 To select a mode E-35 Timekeeping

E-36 Configuring Home City Settings
E-36 To configure Home City settings

E-39 To switch between standard time and summer time manually

Configuring Current Time and Day Settings Manually To change the current time setting manually

E-44 To change the current day setting manually

Taking Direction Readings

To take a direction reading E-50

To perform bidirectional calibration E-58 To perform northerly calibration

Checking the Current Time in a Different Time Zone

To view the time in another time zon

E-64 E-67 To swap your Home City and World Time City

Using the Stopwatch

To enter and exit the Stopwatch Mode

E-70 To perform an elapsed time operation To perform flyback timing

E-72 Using the Countdown Timer

F-73

To specify the countdown start time To perform a countdown timer operation E-74

To stop the alarm

E-75 Using the Alarm

E-76 To change the alarm time setting

To turn the alarm on or off

To stop the alarm

E-79 Adjusting Home Positions

E-81 To adjust home positions

E-83 Troubleshooting

Specifications

Charging the Watch

The face of the watch is a solar panel that generates power from light. The generated power charges a built-in rechargeable battery, which powers watch operations. The watch charges whenever it is exposed to light.

Charging Guide



Whenever you are not wearing the watch, be sure to leave it in a location

where it is exposed to light.

Best charging performance is achieved by exposing the watch to light that is as strong as possible.



When wearing the watch, makes sure that its face is



Leaving the watch in bright light for charging can cause it to become quite hot. Take care when handling the watch to avoid burn injury. The watch can become particularly hot when exposed to the following conditions for long periods.

• On the dashboard of a car parked in direct sunlight

- Too close to an incandescent lamp
- Under direct sunlight

Keep the watch in an area normally exposed to bright light when storing it for long periods. This helps to ensure that power does not run down.
Storing the watch for long periods in an area where there is no light or wearing it in such a way that it is blocked from exposure to light can cause power to run down.

Make sure that the watch is exposed to bright light whenever possible

Checking the Current Power Level

Certain functions will be disabled when the power level is low. If the power level is low, leave the watch in a location where its face (solar panel) is exposed to light.

Low Power

E-14



Low power conditions are indicated by the movement of the [2] Second Hand in the Timekeeping Mode.

If the [2] Second Hand is moving normally at one-second intervals, power is at Level 1.

If the [2] Second Hand is moving at two-second intervals,

- power is at Level 2, which is quite low. Expose the watch to light as soon as possible so it can charge.

Low Battery Alert (Hand Movement and Function

Level	Hand Movement	Function Status
1	Normal.	All functions enabled
2	2 Second Hand moves at two-second intervals.	Beeper and time calibration signal reception disabled.
3	2 Second Hand stopped.	All functions disabled

When power drops to Level 3, all settings (including timekeeping) will be cleared. Recharging the battery will reset all settings to their initial factory defaults.
 When the watch is at Level 3, exposing it to light for a while will cause the [2] Second Hand to move to the position of second 57. This indicates that charging has started.

Power Recovery Mode The watch is designed to go into a power recovery mode that stops hand operation temporarily whenever power suddenly drops below a certain level due to continuous signal reception or other operations over a short period. Note that all operations are disabled while the watch is in the power recovery mode.

The hands will move to the correct positions and the watch will resume normal operation after power recovers (in about 15 minutes). Putting the watch in a location where it is exposed to light will help power to recover sooner.

Charging Times

			Level Chang	e *2
Exposure Level (Brightness)	Daily Operation *1	Level 3	Level 2	Level 1
	Operation		\longrightarrow	·
Outdoor sunlight (50,000 lux)	8 minutes	2	hours	27 hours
Window sunlight (10,000 lux)	30 minutes	6	hours	99 hours
Window sunlight on cloudy day (5,000 lux)	48 minutes	1) hours	161 hours
Indoor fluorescent lighting (500 lux)	8 hours	11	1 hours	

- 1 Approximate exposure each day to generate power for normal daily operation.
 2 Approximate exposure to take power up one level.

 The above times are for reference only. Actual times depend on lighting conditions.
 For details about the operating time and daily operating conditions, see the "Power Supply" section of the Specifications (page E-97).

Power Saving

Power Saving enters a sleep state (second hand sleep or function sleep) whenever the watch is left for a certain period in an area where it is dark.

Elapsed Time in Dark	Operation
60 to 70 minutes (second hand sleep)	2 Second Hand only stopped at 12 o'clock, all other functions enabled
6 or 7 days (function sleep)	All functions, including analog timekeeping, disabled Internal timekeeping maintained

- The watch will not enter a sleep state between 6:00 AM and 9:59 PM. If the watch is already in a sleep state when 6:00 AM arrives, however, it will remain there.
- The watch will not enter a sleep state while it is in the Stopwatch Mode or Countdown Timer Mode.

To recover from the sleep state

Move the watch to a well-lit area or press any button.

F-18 F-19

Radio Controlled Atomic Timekeeping

This watch receives a time calibration signal and updates its time setting accordingly. However, when using the watch outside of areas covered by time calibration signals you will have to adjust the settings manually as required. See "Configuring Current Time and Day Settings Manually" (page E-41) for more information.

This section explains how the watch updates its time settings when the city code selected as the Home City is in Japan, North America, Europe, or China, and is one that supports time calibration signal reception.


If your Home City Code setting is this:	The watch can receive the signal from the transmitter located here:
LON (LONDON), PAR (PARIS), ATH (ATHENS)	Anthorn (England), Mainflingen (Germany)
HKG (HONG KONG)	Shangqiu City (China)
TYO (TOKYO)	Fukushima (Japan), Fukuoka/Saga (Japan)
HNL (HONOLULU), ANC (ANCHORAGE), LAX (LOS ANGELES), DEN (DENVER), CHI (CHICAGO), NYC (NEW YORK)	Fort Collins, Colorado (United States)


Important!


The areas covered by HNL (HONOLULU) and ANC (ANCHORAGE) are quite far from the calibration signal transmitters, so certain conditions may cause reception


F-20 F-21

Approximate Reception Ranges









E-23

- Signal reception may not be possible at the distances noted below during certain times of the year or day. Radio interference may also cause problems with reception.

- times of the year or day. Radio interference may also cause problems with receptic Mainflingen (Germany) or Anthorn (England) transmitters: 500 kilometers (310 miles)

 Fort Collins (United States) transmitter: 600 miles (1,000 kilometers) (310 miles)

 Flukushima or Fukuoka/Saga (Japan) transmitters: 500 kilometers (310 miles)


 Shangqiu (China) transmitter: 500 kilometers (310 miles)

 As of December 2012, China does not use Daylight Saving Time (DST). If China does go to the Daylight Saving Time system in the future, some functions of this watch may no longer operate correctly.

 Using this watch in a country covered by a time calibration signal that is different from the countries it supports may result in incorrect time indication due to local application of daylight saving time (summer time), etc. application of daylight saving time (summer time), etc.

To get ready for a receive operation

- 1. Confirm that the watch is in the Timekeeping Mode. If it isn't, hold down © for at least two seconds to enter the Timekeeping Mode
- 2. Place the watch in a location where signal reception is good.



- . Position the watch as shown in the nearby illustration, with 12 o'clock pointed towards a window. Make sure there are no metal objects nearby.
- · Signal reception normally is better
- at night.

 The receive operation takes from two to 10 minutes, but in some cases it can take as long as 20 minutes. Take care that you do not perform any button operation or move the watch during this time.

E-24 E-25

Signal reception may be difficult or even impossible under the conditions described below.







Near household or a mobile phone







- What you should do next depends on whether you are using Auto Receive or Manual Receive.
- Auto Receive: Leave the watch over night in the location you selected in step 2. See "Auto Receive" on page E-27 for details.

 Manual Receive: Perform the operation under "To perform manual receive" on
- page E-28

Auto Receive

- Auto Receive

 With Auto Receive, the watch performs the receive operation each day automatically up to six times (up to five times for the Chinese calibration signal) between the hours of midnight and 5 a.m. (according to the Timekeeping Mode time). When any receive operation is successful, none of the other receive operations for that day are performed.

 When a calibration time is reached, the watch will perform the receive operation only if it is in the Timekeeping Mode. The receive operation is not performed if a calibration time is reached while you are configuring settings.

E-26 E-27

- In the Timekeeping Mode (page E-35), keep (B) depressed (for about two seconds) as the (2) Second Hand goes through the following sequence.
 Moves to Y (YES) or N (NO) to indicate the last signal reception result, then to R (READY).
- 2. The 2 Second Hand indicates the operations the watch is currently performing.



When the 2 Second Hand is pointed here:	,,
R (READY)	Watch is setting up for reception.
W (WORK)	Reception is in progress.

- If signal reception is unstable, the 2 Second Hand may
 move between W (WORK) and R (READY).
 When the receive operation is successful, the watch
 adjusts the time setting accordingly, and then resumes
 regular timekeeping. It does not adjust the setting if the
 operation failed operation failed

. To interrupt a receive operation and return to the Timekeeping Mode, press any

To check the result of the latest receive operation



In the Timekeeping Mode, press ③ The ② Second Hand will move to Y (YES) or N (NO) to indicate the last calibration signal receive result.

The ② Second Hand will move to Y (YES) if the latest

- receive operation was successful, or N (NO) if it was not. After about 10 seconds, regular timekeeping will
- Press (B) to return to regular timekeeping. The watch will also return to regular timekeeping if you do not perform any operation for about 10 seconds.

F-28 F-29

The [2] Second Hand will indicate N (NO) if you have adjusted the time or day setting manually since the latest receive operation.

To turn auto receive on and off



- 1. In the Timekeeping Mode, press (a). The (2) Second Hand will move to Y (YES) or N (NO) to indicate the last calibration signal receive result.
- 2. Pull out the crown.
 The 2 Second Hand will perform one full revolution and then stop at the current on/off setting.
- 3. Rotate the crown to move the 2 Second Hand to the setting you want.

 To turn on auto receive, select Y (YES).
- To turn off auto receive, select N (NO).
- 4. Push the crown back in to return to the Timekeeping

F-30

Radio-controlled Atomic Timekeeping Precautions

- Strong electrostatic charge can result in the wrong time setting.
 Even if a receive operation is successful, certain conditions can cause the time setting to be off by up to one second.
- The watch is designed to update its day setting automatically for the period from January 1, 2000 to December 31, 2099. Updating of the day setting by signal reception will no longer be performed starting from January 1, 2100.

 If you are in an area where signal reception is not possible, the watch keeps time with the precision noted in "Specifications" (page E-95).

- with the precision noted in "specifications" (page E-95).

 The receive operation is disabled under any of the following conditions.

 While power is at Level 2 or lower (page E-16)

 While the watch is in the power recovery mode (page E-17)

 While the watch is in the function sleep state (power saving, page E-19)

 While the watch is not in the Timekeeping Mode

 While a direction reading or Countdown Timer operation is in progress (even if the watch is in the Timekeeping Mode)
- A receive operation is cancelled if an alarm sounds while it is being performed.

F-31

Mode Reference Guide

Your watch has five "modes". The mode you should select depends on what you want

To do this:	Enter this mode:	See:
Configure Home City and DST (daylight saving time) settings Perform a time calibration signal receive operation or view the last receive result	Timekeepina Mode	
Change the Auto Receive on/off setting Configure time and day settings manually Determine magnetic north	Timekeeping Mode	E-35 E-48
View the current time in one of 29 cities around the globe Configure World Time City and summer time settings Swap the Home City and World Time City	World Time Mode	E-63 E-64 E-67
Use the stopwatch to measure elapsed time	Stopwatch Mode	E-69
Use the countdown timer	Countdown Timer Mode	E-72

To do this:	Enter this mode:	See:
Set an alarm time Turn the alarm ON or OFF	Alarm Mode	E-75 E-78

Selecting a Mode

With this watch, everything starts from the Timekeeping Mode




To determine the watch's current mode Check what the **[5]** Lower Dial Hand is indicating as shown under "To select a mode" (page E-34).

To return to the Timekeeping Mode from any other

Hold down © for at least two seconds

E-33

Each press of \bigcirc will cycle between modes. The currently selected mode is indicated by the $\boxed{5}$ Lower Dial Hand.



Timekeeping

To enter the Timekeeping Mode, hold down © at least two seconds.



Hand Functions

- 1 Hour Hand 2 Second Hand
- 3 Minute Hand
- 4 Upper Dial Hand: Indicates the current hour in the
- Home City time in 24-hour format.

 5 Lower Dial Hand: Points to the day of the week.
- 6 Day Indicator

E-34 E-35

Configuring Home City Settings

The Home City is location where you will normally use the watch. You can choose from a selection of city codes that represent 29 cities around the globe.



To configure Home City settings

- This watch does not have a city code that corresponds
- This will cause the 2 Second Hand to move to the
- city code of the currently selected Home City.

 This indicates the city code setting mode.
- If you do not perform any operation with the crown for about two minutes after pulling it out, errors operations will become disabled and the band will not me. nyou do not periodin any operation will become disabled and the hand will not movif you rotate the crown. If this happens, push the crown back in and then pull it out again.
- . For details about city codes, see the "City Code Table" at the back of this



- 2. Rotate the crown to move the 2 Second Hand to the city
- code you want to select as your Home City.
 Each time you select a city code, the [] Hour Hand,
 [3] Minute Hand and [6] Day Indicator move to the current time and day for that city code.
- 3. Push the crown back in to return to the Timekeeping

E-36 E-37

STD/DST Switching

STD/IDST Switching
You can select summer time or standard time independently for each city. The initial default setting for all cities is AT (AUTO).

Normally you should use the AT (AUTO) setting because it automatically switches between summer time and standard time. You should change the setting to STD (standard time) or DST (summer time) in the following cases.

- When using a time of a location that is not included in the watch's list of 29 cities

- When the preset AUTO standard time/summer time timing is incorrect for some reason

- Daylight Saving Time (DST)

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight

- Note that you cannot switch between STD (standard time) and DST (daylight)
- saving time) while **UTC*** is selected as your Home City. Coordinated Universal Time, the world-wide scientific standard of timekeeping. The reference point for UTC is Greenwich, England.

To switch between standard time and summer time manually

- Perform steps 1 and 2 under "To configure Home City settings" (page E-36).
 Selecting a city code will cause the ① Hour Hand. ③ Minute Hand, and ② Upper Dial Hand to move automatically to the current time for the selected of the code.
 - If you will use the watch in a city that is not included in the city code list, select a
- city code that is in the same time zone as your city.

 Displaying the Home City Settings screen will cause the Stower Dial Hand to move to AT (auto switching), STD (standard time), or DST (daylight saving time).

	AT (AUTO)	The watch automatically switches between standard time and daylight saving time in accordance with its calendar.
	STD	The watch always shows standard time.
İ	DST	The watch always shows daylight saving time.

F-38 F-39



2. Hold down (A) for about one second to cycle through the summer time settings as shown below



3. After the setting is way you want, push the crown back in

Configuring Current Time and Day Settings Manually

You can configure current time and day settings manually when the watch is unable to



To change the current time setting manually

- Pull out the crown.
 This will cause the ② Second Hand to move to the
- This will cause in least section thank to move to the city code of the currently selected Home City.
 If you do not perform any operation with the crown for about two minutes after pulling it out, crown operations will become disabled and the hand will not move if you rotate the crown. If this happens, push the crown back in and then pull it out again.


F-40 F-41



2. Change the Home City settings, if you want.

- For details about these settings, see step 2 under "To configure Home City settings" (page E-36).
- 3. Hold down © for about one second until the watch beeps and the 2 Second Hand moves to 12 o'clock.

 This indicates the manual time setting mode.
 - In the following steps, each press of © cycles between settings as shown below



4. Rotate the crown to adjust the time (hour and minute) setting

- See "Using the Crown" (page E-4) for information about high-speed hand
- The 4 Upper Dial Hand is synchronized with the 1 Hour Hand
- Ine <u>In Upper Dial Hand</u> is synchronized with the <u>III Hour Hand</u>.
 When adjusting the setting, check to make sure that the <u>II Upper Dial Hand</u> correctly indicates an a.m. time or p.m. time.
 If you want to change the day setting at this time, press © and perform the procedure starting from step 3 under "To change the current day setting manually" (page E-44).
- After the settings are the way you want, push the crown back in to return to the Timekeeping Mode.
 - This causes timekeeping to resume with the 2 Second Hand starting from



- Pull out the crown.
 This will cause the ② Second Hand to move to the city code of the currently selected Home City.
- 2 Hold down © for about one second until the watch
- beeps and the 2 Second Hand moves to 12 o'clock

 This indicates the manual time setting mode.
- 3. Press © twice. This will enter the day setting mode The 6 Day Indicator will move slightly to indicate the setting mode.
- 4. Rotate the crown to adjust the day setting



Setting the month

- After the **6** Day Indicator stops moving, press
 This will enter the month setting mode. The **2** Second Hand will move to the currently selected month.
- 6. Rotate the crown to adjust the month setting.
- 7. Press ©. This will enter the year setting
 - node.

 The ① Hour Hand will move to the number that represents the tens digit of the year and the ③ Minute Hand will move to the number that represents the ones digit. The ② Second Hand will move to 12 o'clock and stop there.

E-44 E-45

8. Rotate the crown to adjust the year setting.

• If you want to change the time setting at this time, press © and then perform the procedure starting from step 4 under "To change the current time setting" manually" (page E-41)



Year setting (ones digit)



- 9. After the settings are the way you want, push the crown back in to return to the Timekeeping Mode.
 - This causes timekeeping to resume with the 2 Second Hand starting from 12 o'clock

The watch's built-in full automatic calendar makes allowances for different month lengths and leap years. Once you set the day, there should be no reason to chan it except after you have the watch's rechargeable battery replaced or after power drops to Level 3.

Taking Direction Readings

The watch has a magnetic sensor that makes it possible to take digital compass readings. You can use the digital compass to find the direction to a specific objective

and to determine your current position.

See "Magnetic North and True North" (page E-60) for information about the two types of north. For information about maximizing digital compass accuracy, see "Calibrating Direction Readings" (page E-53) and "Digital Compass Precautions" (page E-60).



Hand Indicators

- 1 Hour Hand
- Second Hand: Points to magnetic north.
- 3 Minute Hand
- 5 Lower Dial Hand: Points to the day of the week

F-48 F-49

CASIO

To take a direction reading



- Point the 12 o'clock position of the watch in the direction you want to read.
- 2. In the Timekeeping Mode, keep the watch horizontal as
 - you press (a).

 The [2] second Hand will move to 12 o'clock* and the direction reading operation will start. After about two seconds, the [2] second Hand will move to indicate
 - north.


 If the [2] Second Hand does not point to 12 o'clock, it could mean that the hand is out of position. Use the procedure under "To adjust home positions" (page E-81) to correct the hand position.
- The 2 Second Hand indicates magnetic north.
- The [2] Second Hand will continue to move for about 20 seconds after you start the digital compass operation as it adjusts its magnetic north reading. After that, the hand will stop at the final reading.

 To take another direction reading, press (a) again.
- To stop an ongoing direction reading operation and return to the Timekeeping Mode, press ©.
- If you do not perform any operation, the watch will return to normal timekeeping after about one or two minutes

3. Press © to return to the Timekeeping Mode.

If the I] Hour Hand stops at 6 o'clock and the I] Minute Hand stops at 12 o'clock, it could mean that the watch has detected abnormal magnetism. For more information, see "Abnormal magnetism detection is indicated." (page E-87).

F-50 F-51



ed by north pointer

Example: Determining your current position and your objective on a map Having an idea of your current location and the direction to your destination is important when mountain climbing or hiking. In this example, we show you how to plot directions on a map and determine your current location using direction measurements taken by the watch.

- In the Timekeeping Mode, press (A).
- 2. Rotate the map (without moving the watch) until north on the map is aligned with north as indicated by the watch's second hand.

 Depending on how the watch is set up, it may be indicating magnetic north or true north.

- Magnetic north: Indicates north in accordance with the Earth's magnetic field. True north: Indicates the direction to the North Pole. For information about setting the watch up to indicate magnetic north or true north, see "Magnetic North and True North" (page E-60).
- Determine your location and destination by checking the map and the geographic contours around you.

Calibrating Direction Readings

You can use the information in this section to calibrate direction readings, which helps to improve digital compass accuracy.

Direction Reading Calibration Methods

To ensure correct direction readings by this watch, be sure to perform bidirectional calibration before using it. The watch may produce incorrect direction readings if you do not perform bidirectional calibration.

Keep the watch away from audio speakers, magnetic necklace, cell phone, and
other devices that generate strong magnetism. Exposure to strong magnetism can
magnetize the watch and cause incorrect direction readings. If incorrect readings
continue even after you perform bidirectional calibration, it could mean that your
watch has been magnetized. If this happens, contact your original retailer or an
authorized CASIO Service Center.

Bidirectional Calibration

Use this method when using the watch to take readings in an area where magnetic force is present, or if you notice that the readings produced by the watch are different from another compass.

Northerly Calibration


 Use this method to calibrate the watch to detect true north (when it is known by vou).

Precautions about bidirectional calibration

- You can use any two opposing directions for bidirectional calibration. You must, however, make sure that they are 180 degrees opposite each other. Remember that if you perform the procedure incorrectly, you will get wrong bearing sensor
- Do not move the watch while calibration of either direction is in progress.
 You should perform bidirectional calibration in an environment that is the same as that where you plan to be taking direction readings. If you plan to take direction readings in an open field, for example, calibrate in an open field.

E-54 E-55

To perform hidirectional calibration



- 1. In the Digital Compass Mode, pull out the crown.
- The 2 Second Hand and 3 Minute Hand will move to 12 o'clock, and the 1 Hour Hand will move to 6 o'clock.
- 2. Press (A) to start calibration of Point 1 Press (4) to start calibration or Point 1.

 After about seven seconds, the [2] Second Hand will move to Y (YES) if Point 1 calibration was successful or to N (NO) if it was not successful.

 If the [2] Second Hand is pointing at N (NO) (unsuccessful), press (A) to perform Point 1 calibration with the press of the preform Point 1 calibration with the press (A) to perform Point 1 calibration with the press (A) to perform Point 1 calibration with the press (A) to perform Point 1 calibration with the press (A) to perform Point 1 calibration with the pressure (A) to perform Point 1 calibration with the pressure (A) to perform Point 1 calibration with the pressure (A) to perform Point 1 calibration (A) to perform Point 1 calibration (A) to perform Point 1 calibration (A) to perform Point (A) to perform
- calibration again.

 If the [2] Second Hand is pointing at Y (YES) (successful), it will move to 6 o'clock after about two seconds.



- 3. Rotate the watch 180 degrees.
- 4. Press (A) to start calibration of Point 2 After about seven seconds, the [2] Second Hand will move to Y (YES) if Point 2 calibration was successful or to N (NO) if it was not successful.

 If the [2] Second Hand is pointing at N (NO) (unsuccessful), press (a) to return to Point 1
- calibration.
- 5. After calibration is complete, push the crown back in and then lock it.

 This will start a magnetic north reading operation · Press (C) to return to the Timekeeping Mode

E-57

To perform northerly calibration

 If you want to perform both northerly and bidirectional calibration, perform by do want to perform but mittenly and confidence admission, perform but bidirectional calibration first, and then perform northerly calibration. This is necessary because bidirectional calibration cancels any existing northerly calibration setting.



- In the Digital Compass Mode, pull out the crown.
- The 2 Second Hand and 3 Minute Hand will move to 12 o'clock, and the 1 Hour Hand will move to 6 o'clock.
- 2. Press ©. The 1 Hour Hand will move to 12 o'clock.
- 3. Place the watch on a level surface, and position it so that its 12 o'clock position points north (as measured with another compass).



- 4. Press (A) to start calibration.
- Press (a) to start calibration.


 After about seven seconds, the [2] Second Hand will move to Y (YES) if calibration was successful or to N (NO) if it was not successful.

 If the [2] Second Hand is pointing at N (NO) (unsuccessful), press (A) to perform calibration again.
- 5. After calibration is complete, push the crown back in
- This will start a magnetic north reading operation.
- . Press (C) to return to the Timekeeping Mode

F-58 F-59

Digital Compass Precautions

Magnetic North and True North



The northerly direction can be expressed either as magnetic north or true north, which are different from each other. Also, it is important to keep in mind that magnetic north moves over time.

*Magnetic north is the north that is indicated by the needle of a compass.

- - True north, which is the location of the North Pole of the Earth's axis, is the north that is normally indicated
- on maps.
 The difference between magnetic north and true north is called the "declination". The closer you get to the North Pole, the greater the declination angle.

Location

- Location

 * Taking a direction reading when you are near a source of strong magnetism can cause large errors in readings. Because of this, you should avoid taking direction readings while in the vicinity of the following types of objects: permanent magnets (magnetic necklaces, etc.), concentrations of metal (metal doors, lockers, etc.), high tension wires, aerial wires, household appliances (TVs, personal computers, washing machines, freezers, etc.).

 **Accurate direction readings are impossible while in a train, boat, air plane, etc.

 **Accurate eardings are also impossible indoors, especially incide ferrogeografe.
- Accurate readings are also impossible indoors, especially inside ferroconcrete structures. This is because the metal framework of such structures picks up magnetism from appliances, etc.

F-60 F-61

Storage

- The precision of the bearing sensor may deteriorate if the watch becomes magnetized. Because of this, you should store the watch away from magnets or any other sources of strong magnetism, including: permanent magnets (magnetic necklaces, etc.) and household appliances (TVs, personal computers, washing machines, freezers, etc.).
- Whenever you suspect that the watch may have become magnetized, perform the procedure under "To perform bidirectional calibration" (page E-56).

Checking the Current Time in a Different Time Zone

You can use World Time to view the current time in one of 29 time zones around the globe. The currently selected city is called the "World Time City".



Hands and Indicators

1 Hour Hand: Indicates the hour of the current time in the World Time City.

Second Hand: Indicates the current World Time City for about three seconds after the World Time mode is entered.

3 Minute Hand

Lower Dial Hand: Points to WT

6 Day Indicator

• Pressing (A) causes the [2] Second Hand to move to the current World Time City for about three seconds.

Important!

E-64

. Time calibration signal reception is disabled while the watch is in the World Time

To view the time in another time zone

- 1. In the Timekeeping Mode, press © once to enter the World Time Mode
 The **5** Lower Dial Hand will move to WT.

2. Pull out the crown.

- The [3] Second Hand points to the currently selected World Time city code.
 The [5] Lower Dial Hand will indicate AT (AUTO), STD (standard time) or
- DST (daylight saving time), which indicates the current daylight saving time
- of transpire saving lines, which motions are covered to a setting.

 If you do not perform any operation with the crown for about two minutes after pulling it out, crown operations will become disabled and the watch hands will no longer move when you rotate the crown. If this happens, push the crown back in and then pull it out again.

3. Rotate the crown to move the $\fbox{2}$ Second Hand to the city code you want to select

- Each time you select a city code, the [] Hour Hand, [3] Minute Hand, and [6] Day Indicator move to the current time and day for that city code. For details about city codes, see the "City Code Table" at the back of this manual.
- If you think that the time indicated for the selected World Time City is not correct. it probably means that there is something wrong with your Home City settings.

 Use the procedure under "To configure Home City settings" (page E-36) to correct the Home City settings.
- 4. Hold down ${\textcircled{A}}$ for about one second to cycle through the summer time settings as



E-65

After selecting the city you want, push the crown back in to return to the World Time Mode.

Swapping your Home City and World Time City

an use the procedure below to swap your Home City and World Time City. This lity can come in handy when you frequently travel between two locations in capability can come different time zones.



The following example shows what happens when the Home City and World Time City are swapped while the Home City originally is **TYO** (Tokyo) and the World Time City is **NYC** (New York).

	Home City	World Time City
Before swapping	Tokyo 10:08 p.m. (Standard time)	New York 9:08 a.m. (Daylight saving time)
After swapping	New York 9:08 a.m. (Daylight saving time)	Tokyo 10:08 p.m. (Standard time)

To swap your Home City and World Time City



- 1. In the World Time Mode, pull out the crown.
- 2. Rotate the crown to move the 2 Second Hand to the city you want to select as your World Time City.

 In this example, you would move the 2 Second Hand to NYC in order to select New York as the World
- Wait until the 11 Hour Hand and 3 Minute Hand complete their move to the time in the currently selected World Time City. You will not be able to perform step 4 of this procedure until the hands stop
- 3. Push the crown back in

E-67

- 4. Hold down (A) for about three seconds until the watch beeps.
- This will make the World Time City (NYC in this example) your new Home City.
 At the same time, it will change the Home City you had selected prior to step 4
 (TYO in this example), to your World Time City.
 After swapping the Home City and World Time City, the watch will stay in the World Time Mode. The 2 Second Hand will point to your new World Time City
 (TYO in this example). (TYO in this example)

If your current World Time City supports time calibration signal reception, making it your Home City enables calibration signal reception for that city.

Using the Stopwatch

You can use the stopwatch to measure elapsed times. A flyback feature (page E-70) lets you reset the stopwatch to zero without stopping time measurement



Hands and Indicators

- Hour Hand: Indicates the stopwatch minute count (1 revolution = 60 minutes).
- Second Hand: Indicates the 1/20 (0.05)-second count during stopwatch operation.
 Minute Hand: Indicates the stopwatch seconds count.
- 4 Upper Dial Hand: Indicates the stopwatch minute count (1 revolution = 120 minutes).
- 5 Lower Dial Hand: Points to ST.

F-68 F-69

To enter and exit the Stopwatch Mode

In the Timekeeping Mode, press © twice to enter the Stopwatch Mode.

• The [5] Lower Dial Hand will move to ST.

To perform an elapsed time operation



To perform flyback timing

F-70

Pressing (B) while an elapsed time operation is in progress performs zero reset and immediately resumes timing from there. You can do this as many times as you want.



• An ongoing elapsed time measurement operation is not affected by pulling out the crown

• The 2 Second Hand, which indicates the 1/20 (0.05)-second count during stopwatch operation, moves only 30 seconds after an elapsed time measurement operation is started or restarted. After that, the 2 Second Hand stops.

F-71

Using the Countdown Timer

The countdown timer can be configured within a range of one minute to 60 minutes. An alarm sounds for about 10 seconds when the timer reaches zero.



Hands and Indicators

- 2 Second Hand: Indicates countdown or elapsed seconds.

 3 Minute Hand: Indicates countdown or elapsed minutes.
- Lower Dial Hand: Points to TR.
 All hands move counterclockwise during a countdown.

To specify the countdown start time



- In the Timekeeping Mode, press © three times to enter the Countdown Timer Mode.
- The 5 Lower Dial Hand will move to TR.
- 2. In the Countdown Timer Mode, pull out the crown. This enters the countdown start time setting mode.
- If you do not perform any operation with the crown for about two minutes after pulling it out, crown operations will become disabled and the hand will not move if you rotate the crown. If this happens, push the crown back in and then pull it out again.
- 3. Rotate the crown to set the countdown start time.
- Notate the crown to set the countdown start time.

 The maximum countdown start time setting is
 60 minutes. To set a countdown start time of
 60 minutes, move the 3 Minute Hand to 12 o'clock.
 See "Using the Crown" (page E-4) for information about high-speed hand movement.

To perform a countdown timer operation



- A time-up alert sounds for 10 seconds when the countdown reaches 0, and then the timer displays the start time.
- The alarm will not sound if battery power is low
- Pulling out the crown while a countdown is in progress will stop the countdown and enter the countdown start time setting mode.

Important!

Time calibration signal reception is disabled while the watch is in the Countdown Timer Mode.

To stop the alarm

Press any button.

Using the Alarm

When the alarm is turned on, an alarm will sound for about 10 seconds each day when the time in the Timekeeping Mode reaches the preset alarm time. This is true even if the watch is not in the Timekeeping Mode.



Hands and Indicators

- 1 Hour Hand: Indicates the currently set alarm time hour. 2 Second Hand: Indicates the current alarm ON/OFF setting.
- 3 Minute Hand: Indicates the currently set alarm time minute.
- 4 Upper Dial Hand: Indicates the hour setting of the current alarm time in 24-hour format.
- 5 Lower Dial Hand: Points to AL.

E-74 E-75

- To change the alarm time setting

 1. In the Timekeeping Mode, press ⓒ four times to enter the Alarm Mode.

 The ⑤ Lower Dial hand will move to AL.
- 2. Pull out the crown to enter the alarm setting mode.
 - If you do not perform any operation with the crown for about two minutes after pulling it out, crown operations will become disabled and the watch hands will no longer move when you rotate the crown. If this happens, push the crown back in and then pull it out again.
 - You can toggle between the hour and minute setting mode, and the hour only setting mode by pressing ©.



- 3. Rotate the crown to set the alarm time
- The T Hour Hand will also move

- See "Using the Crown" (page E-4) for information about high-speed hand movement.
- 4. Press © to switch to the hour setting mode.
 - The The Hour Hand will move slightly left and right to indicate the Thour Hand
 - The Linear Hand will move signify left and right to indicate the Linear Hand setting mode.

 Check the 24-hour time indicated by the 4 Upper Dial Hand to see if the current setting is a.m. or p.m.
- 5. Rotate the crown to adjust the hour setting only.
 - See "Using the Crown" (page E-4) for information about high-speed hand movement.
- 6. After the setting is the way you want, push the crown back in to exit the alarm
 - The alarm always works based on the time kept in the Timekeeping Mode.
 - The watch will return to the Timekeeping Mode automatically if you do not perform any operation in the Alarm Mode for about two or three minutes.

In the Alarm Mode, press (a) to toggle the alarm between on and off. The [2] Second Hand will indicate the current ON/OFF setting.

- The alarm will not sound if battery power is low.
 The alarm will not sound if the watch is in the Power Saving sleep state.

To stop the alarm

Press any button.

Adjusting Home Positions

Strong magnetism or impact can cause the hands and/or day indicator setting to be off, even if the watch is able to perform the time calibration signal receive operation.

Auto Home Position Adjustment

- Auto correction of hand home positions corrects the hand position automatically.
- Auto correction is performed in the Timekeeping Mode only.
 Auto correction corrects the positions of all hands. For the day Indicator, you must perform the manual adjustment procedure under "To adjust home positions" (page E-81).
- If the 4 Upper Dial Hand is 12 hours off of the current correct time, correct the setting using the procedure under "To adjust home positions" (page E-81)

F-78 F-79

Manual Home Position Adjustment

Perform the procedure in this section if auto home position adjustment is not possible for some reason.

Hand home position adjustment is not required if the time and day settings are

- Any time after you enter the home position adjustment mode in step 2 of the following procedure, you can return to the Timekeeping Mode by pushing the crown back in. In this case, any adjustments you made before the watch returned to the Timekeeping Mode will be applied.
- If you do not perform any operation with the crown for about two minutes after pulling it out, crown operations will become disabled and hands will not move if you rotate the crown. If this happens, push the crown back in and then pull it out again.

To adjust home positions



- 1. Pull out the crown.
- 2. Hold down (B) for at least five seconds until the watch beeps and the [2] Second Hand moves to 12 o'clock.
- Automatic home position adjustment of all of the hands (but not the \$\overline{\mathbb{G}}\) Day Indicator) will start.

 If all hands are at 12 o'clock (the proper home hand home position), advance directly to step 3.
- If the **(a)** Upper Dial Hand is not pointing at **24**, which is its home position, hold down **(a)** for about two seconds to move it there.

F-80 F-81



- This enters the 6 Day Indicator home position adjustment mod
- 4. Check the 6 Day Indicator to confirm that it is 1, which is its home position.

 If the 1 is not in the center of the 6 Day Indicator,

 - rotate the crown to center it.

 Rotating the crown three full consecutive turns clockwise will cause the **(§)** Day Indicator to start changing in a forward direction (increment).

 To stop **(§)** Day Indicator movement, press any button.

Push the crown back in to return to the Timekeeping Mode.
 This will cause the hands to return to their normal positions and resume regular timekeeping. Wait until everything stops moving before performing any other operation.

Troubleshooting

Hand Movement and Position

■ I lost track of what mode the watch is in.

Refer to "Mode Reference Guide" (page E-32). To return directly to the Timekeeping Mode, hold down © at least two seconds.

- The [2] Second Hand is moving at two-second intervals.
 All the watch's hands are stopped at 12 o'clock and none of the buttons work ([2] Second Hand stopped at 57, 58, 59, or 00).
 Power may be low. Expose the watch to light until the [2] Second Hand starts moving normally, at one-second intervals (page E-16).

■ The hands of the watch suddenly start moving at high speed, even when I do

not perform any operation.

This could be due to any one of the following causes. In all cases, the hand movement does not indicate malfunction, and should stop shortly.

The watch is recovering from a sleep state (page E-19).

E-83

. The time setting is being adjusted following a successful auto time calibration signal receive operation (page E-20).

■ Hands suddenly stop moving. Button operation also is disabled.

The watch may be in the power recovery mode (page E-17). Do not perform any operation until the hands return to their normal positions (in about 15 minutes). The hands should return to their correct positions when normal operation returns. To help power recover, leave the watch in a location where it is exposed to light.

■ The current time setting is off by hours.

- Your Home City setting may be wrong. Check your Home City setting and correct it, if necessary (page E-36).
- The current time setting is off by one hour.
- If you are using the watch in an area where time calibration signal reception is possible, see "To configure Home City settings" (page E-36).
- The period when summer time is applied in the location where you are using the watch may be different from the period set for your currently selected Home City. Use the procedure under "To switch between standard time and summer time manually" (page E-39) to switch from AT (AUTO) to STD (for standard time) or DST (for summer time).
- The time and date settings are off.

This could indicate that the watch has been exposed to magnetism or strong impact, which has caused problems with proper hand and day indicator alignment. Adjust the watch's hand and day indicator home position alignment (page E-79).

E-84 E-85

■ An error is indicated during sensor operation.

Subjecting the watch to strong impact can cause sensor malfunction or improper contact of internal circuitry. When this happens an error is indicated and the sensor operation cannot be performed. The illustrations below how sensor mode errors are indicated.



- During digital compass operations, nearby strong magnetism can cause an error to be indicated.
 If the error is indicated during a measurement, restart the measurement. If an error is indicated when you restart the measurement, it probably means that there is a problem with the sensor or internal circuitry

Abnormal magnetism detection is indicated.



- Move the watch away from magnetic accessories, electric devices, computers, and any other devices that generate strong magnetism, and try performing the sensor operation again.
 If abnormal magnetism detection is indicated again,
- If anormal magnetism detection is indicated again, it may mean that the watch case may have become magnetized or that magnetism conditions are completely different from those where you last performed bidirectional calibration. Perform bidirectional calibration using the procedure under "To perform bidirectional calibration" (page E-56).

Whenever you have a sensor malfunction, take the watch to your original dealer or nearest authorized CASIO distributor as soon as possible.

E-86 E-87

■ What causes incorrect direction readings?

- The watch may have been exposed to magnetism. Calibrate the direction sensor.
 A nearby source of strong magnetism, such as a household appliance, a large steel bridge, a steel beam, overhead wires, etc., or an attempt to perform direction measurement on a train, boat, etc. Move away from such objects and try again.

■ What causes different direction readings to produce different results at the

· Magnetism generated by nearby digital noise sources (such as high-tension power lines) can interfere with the detection of terrestrial magnetism. Move away from the source of the digital noise and try again.

■ Why am I having problems taking direction readings indoors?

A TV, personal computer, speakers, or some other object is interfering with terrestrial

A TV, personal computer, speakers, or some other object is interiering with terrestrial magnetism readings. Move away from the object causing the interference or take the direction reading outdoors. Indoor direction readings are particularly difficult inside ferro-concrete structures. Remember that you will not be able to take direction readings inside of trains, airplanes, etc.

■ The watch does not resume operation after I expose it to light.

This can happen after the power level drops to Level 3 (page E-16). Continue exposing the watch to light until the 2 Second Hand starts moving normally (at one-second intervals).

■ The [2] Second Hand starts to move at one-second intervals, but then suddenly returns to moving at two-second intervals. The watch probably is not sufficiently charged yet. Continue keeping it exposed to

Time Calibration Signal

The information in this section applies only when LONDON (LON), PARIS (PAR), ATHENS (ATH), HONOLULU (HNL), ANCHORAGE (ANC), LOS ANGELES (LAX), DENVER (DEN), CHICAGO (CHI), NEW YORK (NYC), HONG KONG (HKG), or TOKYO (TYO) is selected as the Home City. You need to adjust the current time manually when any other city is selected as the Home City.

F-88 F-89

■ The 2 Second Hand indicates N (NO) when I check the result of the latest

Possible Cause	Remedy	Page
You are wearing or moving the watch, or performing a button operation during time calibration signal receive operation. The watch is in an area with poor reception conditions.	Keep the watch in an area where reception conditions are good while time calibration signal receive operation is being performed.	E-25
You are in an area where signal reception is not possible for some reason.	See "Approximate Reception Ranges".	E-22
The alarm time was reached during time calibration signal reception.	The alarm sounded during time calibration signal reception, causing reception to be canceled.	_
The calibration signal is not being transmitted for some reason.	Check the website of the organization that maintains the time calibration signal in your area for information about its down times. Try again later.	_

■ The current time setting changes after I set it manually.

You may have the watch configured for Auto Receive of the time calibration signal (page E-27), which will cause the time to be adjusted automatically according to your currently selected Home City. If this results in the wrong time setting, check your Home City setting and correct it, if necessary (page E-36).

■ The current time setting is off by one hour.

Possible Cause	Remedy	Page
in the location where you are using the	Use the procedure under "To switch between standard time and summer time manually" to switch from AT (AUTO) to STD (for standard time) or DST (for summer time).	E-39

F-91

■ Auto Receive is not performed or I cannot perform Manual Receive.

Possible Cause	Remedy		
The watch is in the World Time Mode. The watch is in the Stopwatch Mode.	Auto Receive is not performed while the watch is in the World Time Mode or Stopwatch Mode. Hold down © at least two seconds to enter the Timekeeping Mode.	E-27 E-34	
Your Home City setting is wrong.	Check your Home City setting and correct it, if necessary.	E-20 E-36	
Auto time calibration signal reception is OFF.	Check the auto time calibration signal reception setting.	E-30	
A direction reading or countdown timer operation is in progress.	Stop the ongoing operation.	E-48 E-72	
There is not enough power for signal reception.	Expose the watch to light to charge it.	E-14	

\blacksquare Signal reception is being performed successfully, but the time and/or day is

Possible Cause	Remedy		
Your Home City setting is wrong.	Check your Home City setting and correct it, if necessary.	E-20 E-36	
The watch may have been exposed to magnetism or strong impact, which has caused problems with proper hand and day indicator alignment.	Adjust the watch's hand and day indicator home positions.	E-79	

World Time

The indicated World Time is wrong.
There is a problem with your Home City settings.
Check your Home City settings.
See "To configure Home City settings" (page E-36).

E-93

■ The indicated World Time is one hour off.

The daylight saving time (summer time) setting for the World Time city is wrong. See "To view the time in another time zone" (page E-64).

■ The alarm does not sound.

- Power may be low. Expose the watch to light until the 2 Second Hand starts moving normally, at one-second intervals (page E-16).
- The time setting is wrong in terms of a.m. and p.m.The crown may be pulled out. Push the crown back in.

Specifications

Accuracy at normal temperature: ±15 seconds a month (with no signal calibration)
Timekeeping: Hour, minutes (hand moves every 10 seconds), seconds, day
Calendar system: Full Auto-calendar pre-programmed from the year 2000 to 2099
Other: Home City code (can be assigned one of 29 city codes and Coordinated
Universal Time); Daylight Saving Time (summer time) auto switching /
Standard time, Day of the week

Time Calibration Signal Reception: Auto receive up to six times a day (5 times a
day for the Chinese calibration signal; Remaining auto receives
cancelled as soon as one is successful); Manual receive
Receivable Time Calibration Signals:
Mainfilingen, Germany (Call Sign: DCF77, Frequency: 77.5 kHz);
Anthorn, England (Call Sign: MSF, Frequency: 60.0 kHz); Fukushima,
Japan (Call Sign: JJY, Frequency: 40.0 kHz); Fukushima, (Call Sign: JJY, Frequency: 60.0 kHz); Shangqiu City,
Henan Province, China (Call Sign: BPC, Frequency: 68.5 kHz) Accuracy at normal temperature: ±15 seconds a month (with no signal calibration)

E-94 E-95

Compass: 20 seconds continuous reading; North indication by hand; Calibration (bidirectional, northerly); Manual reading

World Time: 29 cities (29 time zones) and Coordinated Universal Time
Other: Daylight Saving Time (summer time) / Standard Time
Stopwatch: Measuring capacity: 1:59'59.95"
Measuring unit: 1/20 (0.05) seconds
Measuring mode: Elapsed time
Flyback timing

Countdown Timer:

Measuring unit: 1 second Input range: 1 to 60 minutes (1-minute increments)

Alarm: Daily alarm

Other: Power Saving; Auto Correction of Hand Home Positions

Power Supply: Solar panel and one rechargeable battery

Approximate battery operating time: 6 months (no exposure to light after a full charge; 10 seconds beeper operation, one signal reception of approximately 4 minutes per day; 20 direction reading operations per month)

E-97



City Code Table



CASIO®

City Code Table

UTC Offset/ Summer Time Period					
City Code		City	GMT Differential	Summer Time Start	Summer Time End
PAGO PAGO	(PPG)	Pago Pago	-11	None	None
HONOLULU	(HNL)	Honolulu	-10	None	None
ANCHORAGE	(ANC)	Anchorage	-9		
LOS ANGELES	(LAX)	Los Angeles	-8	02:00. second	02:00, first Sunday
DENVER	(DEN)	Denver	-7	Sunday in March	in November
CHICAGO	(CHI)	Chicago	-6		
NEW YORK	(NYC)	New York	-5	1	
SANTIAGO	(SCL)	Santiago	-4	24:00, second Saturday in October	24:00, second Saturday in March
RIO		Rio De Janeiro	-3	0:00, third Sunday in October	0:00, third Sunday in February or 0:00, fourth Sunday in February

City Code		City	UTC Offset/ GMT Differential	Summer Time Period	
				Summer Time Start	Summer Time End
F. DE NORON	IHA(FEN)	Fernando de Noronha	-2	None	None
PRAIA	(RAI)	Praia	-1	1	
UTC					
LONDON	(LON)	London	0	01:00, last Sunday in March	02:00, last Sunday in October
PARIS	(PAR)	Paris	+1	02:00, last Sunday in March	03:00, last Sunday in October
ATHENS	(ATH)	Athens	+2	03:00, last Sunday in March	04:00, last Sunday in October
JEDDAH	(JED)	Jeddah	+3	None	None
TEHRAN	(THR)	Tehran	+3.5	0:00, March 22 or 0:00, March 21	0:00, September 22 or 0:00, September 21

L-2 L-3

City Code		City	UTC Offset/ GMT Differential	Summer Time Period	
				Summer Time Start	Summer Time End
DUBAI	(DXB)	Dubai	+4	None	None
KABUL	(KBL)	Kabul	+4.5		
KARACHI	(KHI)	Karachi	+5		
DELHI	(DEL)	Delhi	+5.5		
DHAKA	(DAC)	Dhaka	+6		
YANGON	(RGN)	Yangon	+6.5		
BANGKOK	(BKK)	Bangkok	+7		
HONG KONG	(HKG)	Hong Kong	+8		
TOKYO	(TYO)	Tokyo	+9		
ADELAIDE	(ADL)	Adelaide	+9.5	02:00, first Sunday in October	03:00, first Sunday in April
SYDNEY	(SYD)	Sydney	+10		
NOUMEA	(NOU)	Noumea	+11	None	None
WELLINGTON	(WLG)	Wellington	+12	02:00, last Sunday in September	03:00, first Sunday in April

- This table shows the city codes of this watch. (As of December 2012)
 The rules governing global times (UTC offset and GMT differential) and summer time are determined by each individual country.
 The summer time periods in this table are applicable to specific cities. For cities not included in the list, select the list city that is in the same time zone as the desired city and perform STD/DST settings manually.

L-5